

## **19. Mining & Extraction of Natural Resources**

The following conditions represent the minimum standards for review and specific conditions, unique to the site proposed, shall be determined as part of the review and approval process.

1. Pits and quarries shall be completely enclosed by a fence four (4) or more feet in height for the safety of the public. Said fence shall be placed no closer than ten (10) feet to the outside perimeter of the pit or quarry. Said fence shall conform with the minimum setback requirements of the district in which it is located.
2. No slope shall exceed an angle with the horizontal of more than thirty (30) degrees for the first twelve (12) feet along the horizontal, after which the slope shall not exceed an angle with the horizontal of more than forty-five (45) degrees.
3. The applicant shall submit a three-part topographic site plan identifying: 1) the existing site and elevations; 2) the areas proposed for mining; and 3) the finished grade and intended use of the site once reclaimed. All areas so used shall be rehabilitated progressively as they are worked out or abandoned to a condition entirely free from hazards and blending with the surrounding natural grounds. All slopes and banks shall be graded to prevent excessive erosion. The Planning Commission, upon recommendation from the County Road Department, shall establish routes of ingress and egress for truck movement to minimize the wear on public roads and to prevent hazards to traffic. All interior roadways shall be chemically treated to reduce dust.

Allowed by SLU Permit only in the Agricultural Zoning District which is a contravention of State law.